

Color your work.



Over 100 years old German Lubricant Equipment manufacturer **PRESSOL** introduces its **Super Heavy Duty Grease Gun** for Professionals to the US market



**Engineered  
in Germany**  
Made in the  
European Union

**PRESSOL**

## PRELixx PRO GREASE GUNS



### Technical Data

Grease gun connection, pressure-side	1/8 NPT
Filling nipple and ventilating valve Capacity	16 ounce
Refilling options	14 ounce cartridge, grease filling system or loose grease using a spatula
Diameter of grease piston	11/32" (0.354)
Grease pump piston actuation	Manually, lever operated
Delivery rate	18 stokes for 1 oz. Tested with 14 ounce grease cartridge (12 511)
Discharge pressure	Develops up to 10,000 psi
Burst pressure system	13,000 psi
Burst pressure grease gun head	17,000 psi
Operation of plunger rod	With t-grip
Sealing cover	Loose
Wall thickness of grease gun tube	0.039"
Grease gun tube colour	black / silver / red / blue / green / yellow / Galvanized
Dimensions lxWxh	15.55" x 5.51" x 2.60"
Weight (Lbs)	2.82



## ONE HAND GREASE GUNS



### Technical Data

Grease gun connection, pressure-side	1/8 NPT
Filling nipple and venting valve	
Capacity	16 ounce
Refilling options	14 ounce cartridge, Grease gun filling system, bulk grease
Grease pump piston actuation	Manual by means of pressure grip
Delivery rate	18 stokes for 1 oz. Tested with 14 ounce grease cartridge (12 511)
Calibration Volume	
Delivery	27 stokes for 1 oz.
Max. delivery pressure	3,000 psi
Calibration Pressure	
Delivery	42 stokes for 1 oz.
Max. delivery pressure	4,300 psi
Wall thickness of grease gun tube	0.039"
Grease gun tube colour	black/silver/red/blue/green/yellow/galvanized
Dimensions lxWxh	15.55" x 5.51" x 2.60"
Weight (Lbs)	2,86

## HIGH PRECISION COUPLER



Suitable for every commercially available hydraulic grease nipple

Made in Germany

- Connection 1: for H-nipples
- Connection 2: 1/8 NPT female (12 843)
- Design: 4 jaws, turned (one-piece)
- Wrench size (SW): 1/2"
- Material: steel, zinc plated
- Diameter: 9/16"
- Length: 1.5"

[www.pressol.com](http://www.pressol.com)

**PRESSOL**