



Standard grease gun-HHFP

G 1/8"-GBDR-MU-VVP

Item number: 12 634 125
EAN: 4103810423383
Discount group: A

Technical data

Grease gun connection, pressure-side: G 1/8"
 Capacity (cm³): 500
 Refilling options: 400 g grease cartridge, DIN 1284, or bulk grease
 Diameter of grease piston (mm): 8
 Grease pump piston actuation HHFP: manually lever operated
 Delivery rate/stroke (cm³): 1,2, at a counter-pressure of 400 bar
 Discharge pressure up to (bar): 400
 Burst pressure system (bar): 850
 Burst pressure grease gun head (bar): 1200
 Operation of push rod: with L-design handle
 Cover: loose
 Wall thickness of grease gun tube (mm): 1
 Lacquering: silver
 Weight (kg): 1,28

Specification

- Spout, angled, G 1/8", 150 mm (12 735)
- Coupler, 4 jaws, G 1/8" (12 731)
- Sales package, with Bar code

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- TÜV - certified
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm): 400 x 140 x 75
 Weight including package (kg): 1,38
 Packing unit: 1,0